


Panel-Lab Roc Alu Inox

Mineral wool core panel
for white rooms



CE

- The mineral wool core of the Panel-Lab Roc Alu insulating panel provides high compressive strength, excellent thermal and acoustic insulation, and outstanding durability.
- The high performance of Panel-Lab Roc Alu, such as its rigidity, strength and durability, makes it an ideal panel for the construction of walls and ceilings in clean rooms.

Panel-Lab Roc Alu




Description and applications

- Sandwich panel with a rock wool core, available in two possible densities, and stainless steel faces with a thickness of 0.6 mm.
- Wide range of highly durable coatings, adapted to the environment in which the panel will be installed.
- The panel, which incorporates an aluminium framing profile, has been designed for the construction of walls, ceilings and partitions in clean rooms, laboratories, research centres, the pharmaceutical sector, etc.



Technical features



Useful width	1.200 mm			
Manufacturing length ⁽¹⁾	0.5 to 4.1 m			
Core density	Mineral wool LD: 130 kg/m ³ Mineral wool HD: 150 kg/m ³			
Panel thickness (mm)	40	50	60	80
Self-weight ⁽²⁾ (kg/ml)	LD Core 19.10	20.55	22.27	25.75
	HD Core 20.03	21.72	23.68	27.64
Thermal transmittance ⁽³⁾ (W/m².K)	LD Core 0.86	0.70	0.6	0.46
	HD Core 0.90	0.74	0.62	0.48

(1) Non-standard measurements available upon request.

(2) Considering 0.6 mm thick sheets and aluminium trim on two edges.

(3) Obtained by simplified method for the calculation of the thermal transmittance of a panel, considering 0.6 mm thick sheets.

Panel-Lab Roc Alu



Certifications and applicable regulations

Reaction-to-fire classification

- The Panel-Lab Roc Alu panel has the reaction to fire classification A2 - s1, d0 according to EN 13501-1:2018 (Euroclasses).

Product certifications

- CE mark according to EN 14509:2013.



Components

Insulating core

- Mineral wool with density 130 kg/m² (LD) or 150 kg/m² (HD).

Panel facing

- Stainless steel A304
- Standard sheet thickness 0.6 mm

Gasket joint

- Gasket joint, with an aluminium profile, which allows the wall or ceiling support profiles to be placed inside.



Finishes

Profiling option

- Flat finish.

Kingspan | invespanel is a trademark of Teczone Española S.A.U., and reserves the right to modify the contents of this document without any prior warning. Every effort has been made to ensure that the content of this publication is accurate, but Teczone Española S.A.U. and its affiliated companies are not responsible for errors or information that may be misleading. Suggestions regarding the final use or application of the products or work methods are merely informative and Teczone Española S.A.U. and its affiliates do not accept any responsibility in this regard.

Kingspan | Invespanel

Pol. Buicio, Sector 6 Nave 4
E - 26360 Fuenmayor (La Rioja)
T: +34 941 450 923
E: info@invespanel.com
www.invespanel.com

